





























Current Vehicle Location

Overspeed Alert



Road Traffic

Historical Trip Review (60 days details)

Sharing

Multiple Geo-fencing

Vibration Detect

Engine On / Off

External Power Cut (with siren)

















**Find Your** Car















Once the device is plugged in, download the HC-Cargo mobile app and log in to start managing your vehicle.





























#### www.carpro.com.my

















itiple D

















Tyre Vi



Battery Replacement



Renewal







www.carpro.com.my



























Current Vehicle Location

Overspeed Alert

Street View

Road Traffic

Historical (60 days details)

Trip Review

Sharing

Multiple Geo-fencing

Vibration Detect

**Engine** On / Off

Power Cut (with siren)

#### **Specifications**

| Working voltage:         | +6.0 ~+60VDC                             |
|--------------------------|--|
| Power Consumption:       | Standby current:8mA                      |
|                          | Working current: 30mA;                   |
|                          | Peak current: 80mA;                      |
| Inside Backup battery:   | Rechargeable 3.7V 210mAh Li-ion battery  |
| Size of the main unit:   | 58*40*15 (mm)                            |
| Weight of the main unit: | 34g                                      |
| Working temperature:     | -20 ~ 80℃                                |
| Humidity:                | 0 ~ 95%                                  |
| GSM frequencies:         | Quad-band: 850MHz/900MHz/1800MHz/1900MHz |
| GPS chip:                | U-blox 7 chipset                         |
| Receiving ways           | 56 channels                              |
| Working frequencies      | 1575.42Mhz C/A (GPS)                     |
| Receiving sensibility    | -162dBm                                  |
| Positioning accuracy     | ≤10m (wide-open area)                    |
| Speed accuracy           | ≤0.2M/S (wide-open area)                 |
| Positioning mode         | Auto 2D/3D                               |
| Hot start                | 1 sec., average                          |
| Warm start               | 2 sec., average                          |
| Cold start               | 40 sec., average                         |





**HC-CARGO** Malaysia App













